

What is claimed is:

- 1-7 + 14-20 Sub
ok for 52/742.14 P1
- 5
- 10
- 15
- 20
- 25
- 30
1. A method for preparing and installing a baseplate for supporting rotating machinery, comprising:
 - preparing and pouring a grouting material into a cavity in a baseplate;
 - curing said grouting material to achieve desired physical properties for said grouting material;
 - checking the mounting surfaces adapted for supporting a piece of rotating machinery on said baseplate for specified tolerances;
 - placing said baseplate in a fixture to allow machining of said mounting surfaces;
 - machining said mounting surfaces adapted for supporting a piece of rotating machinery on said baseplate to a specified tolerance; and,
 - installing a piece of rotating machinery on said machined mounting surfaces.
 2. A method for preparing and installing a baseplate for supporting rotating machinery, according to Claim 1, including the steps of:
 - accelerating the curing of said grouting material by maintaining said baseplate at an elevated temperature for a specified time period.
 3. A method for preparing and installing a baseplate for supporting rotating machinery, according to Claim 2, further including the steps of:
 - securing said baseplate to a foundation;
 - leveling said baseplate;
 - placing a form around said baseplate and said foundation; and,
 - pouring a grouting material into the void between said baseplate and said foundation.
 4. A method for preparing and installing a baseplate for supporting rotating machinery, according to Claim 3, wherein:
 - said grouting material is an organic grout.
 5. A method for preparing and installing a baseplate for supporting rotating machinery, according to Claim 1, including the steps of:
 - ensuring the curing of said grouting material by curing said grouting material for a specified time period.
 6. A method for preparing and installing a baseplate for supporting rotating

A2 Cont 2

machinery, according to Claim 5, further including the steps of:

securing said baseplate to a foundation;

leveling said baseplate;

placing a form around said baseplate and said foundation; and,

5 pouring a grouting material into the void between said baseplate and said foundation.

7. A method for preparing and installing a baseplate for supporting rotating machinery, according to Claim 6, wherein:

said grouting material is an inorganic grout.

8. A pregrouted baseplate for supporting rotating machinery, comprising:

a frame of a rectangular parallelepiped configuration, said frame open on one side to form a cavity for receiving a grouting material;

a plurality of support members disposed in said cavity to support said rectangular parallelepiped frame;

10 said cavity having a grouting material poured into said cavity and cured in said cavity, said grouting material being cured to achieve desired physical properties; and,

said rectangular parallelepiped frame including a plurality of mounting surfaces adapted for supporting a piece of rotating machinery, said mounting surfaces machined to a specified tolerance after said grouting material is cured.

15 9. A pregrouted baseplate for supporting rotating machinery, according to Claim 8, wherein:

said grouting material is an organic grout.

10. A pregrouted baseplate for supporting rotating machinery, according to Claim 8, wherein:

25 said grouting material is an inorganic grout.

11. A pregrouted baseplate for supporting rotating machinery, comprising:

a frame of a rectangular configuration with an open cavity therein;

a plurality of support members secured to said rectangular frame;

said cavity having a grouting material poured into said cavity and cured in said

30 cavity, said grouting material being cured to achieve desired physical properties; and,

said rectangular frame including a plurality of mounting surfaces adapted for

11

supporting a piece of rotating machinery, said mounting surfaces machined to a specified tolerance after said grouting material is cured

12. A pregrouted baseplate for supporting rotating machinery, according to Claim 11, wherein:

5 said grouting material is an organic grout.

13. A pregrouted baseplate for supporting rotating machinery, according to Claim 11, wherein:

said grouting material is an inorganic grout.

14. A method for preparing and installing a baseplate having an open frame configuration for supporting rotating machinery, comprising:

securing a grout retaining means to a baseplate to form a cavity therein;

preparing and pouring a grouting material into said cavity in said baseplate;

curing said grouting material to achieve desired physical properties for said grouting material;

removing said grout retaining means from said baseplate;

checking the mounting surfaces adapted for supporting a piece of rotating machinery on said baseplate for specified tolerances;

placing said baseplate in a fixture to allow machining of said mounting surfaces;

machining said mounting surfaces adapted for supporting a piece of rotating

20 machinery on said baseplate to a specified tolerance; and,

installing a piece of rotating machinery on said machined mounting surfaces.

15. A method for preparing and installing a baseplate for supporting rotating machinery, according to Claim 14, including the steps of:

accelerating the curing of said grouting material by maintaining said baseplate at an elevated temperature for a specified time period.

16. A method for preparing and installing a baseplate for supporting rotating machinery, according to Claim 15, further including the steps of:

securing said baseplate to a foundation;

leveling said baseplate;

30 placing a form around said baseplate and said foundation; and,

pouring a grouting material into the void between said baseplate and said

4
A Cont'd
foundation.

11 17. A method for preparing and installing a baseplate for supporting rotating machinery, according to Claim 16, wherein:

said grouting material is an organic grout.

5 12 18. A method for preparing and installing a baseplate for supporting rotating machinery, according to Claim 14, including the steps of:

ensuring the curing of said grouting material by curing said grouting material for a specified time period.

10 19. A method for preparing and installing a baseplate for supporting rotating machinery, according to Claim 18, further including the steps of:

securing said baseplate to a foundation;

leveling said baseplate;

placing a form around said baseplate and said foundation; and,

pouring a grouting material into the void between said baseplate and said

15 foundation.

14 20. A method for preparing and installing a baseplate for supporting rotating machinery, according to Claim 18, wherein:

said grouting material is an inorganic grout.